Environmental Control Unit Accessories

Switch Description

Bebco Model EDS Explosion-Proof Disconnects provide three 30-100 amp rated poles to remove all power safely from Bebco Air Conditioners, Pressurization Units, Ventilation Fans, Gas Phase Filtration Units and other products. These switches are intended and suitable for outdoor mounting near our products to safely disconnect power from these devices.



Model EDS Electrical Disconnect Switches

Class I, Division 1, Group B, C & D **Unit Power Disconnects**

Technical Bulletin EDS TB-R1

© 12.10.2020

EDS-30-3 Specifications

Contact Rating: Circuit Wiring: Body Material: Cover Material: Operator Paddle: Overall Height: Overall Width: Overall Depth: Switch Action: Voltage Rating: Circuit Rating: Terminal Type: Lockout Method: Mounting Style: Conduit Ports: Certifications: UL Listed, CSA Certified, CE Marked

30 Amps, Maximum 3-Pole, Non-Fused Cast Aluminum Thermoplastic Black Phenolic Toggle 6.36 Inches 3.95 Inches 4.35 Inches Maintained Position 600 VAC / 230 VDC, Maximum 5000 Amp Short Circuit Rating Screw Clamp Terminals Padlock Shackle Hole 2-Point Surface Mount Top & Bottom, 3/4" Female Thread

EDS-63-3, EDS-80-3 & EDS-100-3 Specifications

Contact Ratings: Circuit Wiring: Body & Cover Material: Operator Paddle: Overall Height: Overall Width: Overall Depth: Switch Action: Voltage Rating: Circuit Rating: Terminal Type: Lockout Method: Mounting Style: Conduit Ports: Certification:

63. 80 or 100 Amps, Maximum 3-Pole, Non-Fused Cast Aluminum Red Phenolic Paddle 13.06 Inches 8.13 Inches 7.82 Inches Maintained Position 600 VAC / 230 VDC, Maximum 5000 Amp Short Circuit Rating Screw Clamp Terminals Padlock Swing Bracket 4-Point Surface Mount Top & Bottom, 3/4" Female Thread CSA C/US Certified



Model EDS-30-3 **Power Disconnect**











(REPRESENTATIVE IMAGE)

IMPORTANT NOTES: All specifications subject to change without notice. Warranty & Liability policies available upon request.

